/leca

Steca PLI

300, 300-L60

The Steca PLI-300 is a low-cost 300 W sine wave inverter for supplying small AC appliances. It has a manual on/off switch allowing the inverter to be switched off to reduce own consumption. The device is especially suitable for use in solar home systems where manually switched small AC appliances are occasionally used in addition to the normal DC appliances. The device is supplied with DC cables and has a european AC power socket.

Product features

- True sine wave voltage
- Optimal battery protection
- Protective insulation according to protection class II

Electronic protection functions

- Deep discharge protection
- Battery overvoltage shutdown
- Overtemperature and overload protection
- Short circuit protection on the AC output side

Displays

• 2 LEDs show operating states

Operation

Main switch

Certificates

• Compliant with European Standards (CE)



	300	300-L60	
		300-L60	
Characterisation of the operating per			
System voltage		12 V	
Continuous power	30	300 VA	
Power 30 min.		300 VA	
Power 5 sec.		350 VA	
Power asymmetric		250 VA	
Max. efficiency	85	85 %	
Own consumption standby	0.	0.5 W	
Own consumption ON	9.1	9.0 W	
DC input side			
Battery voltage	10.5 V	10.5 V 15 V	
Reconnection voltage (LVR)	12	12.5 V	
Deep discharge protection (LVD)	10	10.5 V	
AC output side	·		
Output voltage	230 V AC ±10 %	115 V AC ±10 %	
Output frequency	50 Hz	60 Hz	
Safety			
Protection class	II (double	II (double insulated)	
Electrical protection	reverse polarity AC, ov	no reverse polarity protection for the battery, reverse polarity AC, over voltage, over current, over temperature	
Operating conditions			
Ambient temperature	-20 °C .	-20 °C +50 °C	
Fitting and construction			
AC output side connection	Europe	European plug	
Cable cross-section battery	4 mm ² (4 mm² (AWG 12)	
Degree of protection	IP	IP 20	
Dimensions (X x Y x Z)	245 x 11	245 x 117 x 62 mm	
Weight	1,1	1,2 kg	

